

J-SD-MP MULTI-FIBER CABLE ASSEMBLIES FOR SFP/QSFP/CXP

Features:

- High Density
- High Reliability
- Low Bending Radius
- Custom Defined Specifications
- Environmentally Stable

Applications:

- SFP
- QSFP
- QDR
- CXP



Performance Specifications:

ITEM	
Insertion Loss, dB	$IL \leq 0.7\text{dB} + 0.003 * L \text{ dB}$
Cable Type	Ø2.0 , Ø3.0 Round cable, or others
Connector Type for Both Ends	MPO/PC , MPO/APC , MTRJ , etc.
Cable Length and Tolerance, mm	$L \pm 0.2\% \text{cm}$
Operating Temperature, °C	-20~+70
Storage Temperature, °C	-20~+70
Nos. of Channels	2/4/8/12 or specified by customer

Configuration:



Unit: mm

Straight (Type A)		Total flipped (Type B)		Pair flipped (Type C)	
Fiber	Fiber	Fiber	Fiber	Fiber	Fiber
1	1	1	12	1	2
2	2	2	11	2	1
3	3	3	10	3	4
4	4	4	9	4	3
5	5	5	8	5	6
6	6	6	7	6	5
7	7	7	6	7	8
8	8	8	5	8	7
9	9	9	4	9	10
10	10	10	3	10	9
11	11	11	2	11	12
12	12	12	1	12	11