



OZ Optics

www.ozoptics.com

219 Westbrook Rd, Ottawa, ON, Canada, K0A 1L0 Toll Free: 1-800-361-5415 Tel:(613) 831-0981 Fax:(613) 836-5089 E-mail: sales@ozoptics.com

FIBER OPTIC ISOLATORS

Features:

- >10W Optical power handling capability - **NEW**
- Polarization Sensitive and Insensitive versions - **NEW**
- Product offerings over 488 nm-1600 nm wavelength range
- High isolation levels and low return loss
- Low Insertion Loss and Polarization Dependent Losses
- Different compact sizes, including miniature packaged versions
- Stable and high reliability designs

Applications:

- High power laser to fiber coupling systems
- Optical amplifiers
- CATV systems

Product Description:


OZ Optics offers a complete line of fiber pigtailed isolators for wavelengths ranging from 488nm to 1650nm. These isolators combine a free space Faraday rotator with polarizing optics to provide up to 60 dB of isolation and high power handling with minimum losses.

Our isolators are manufactured using OZ Optics's patented tilt alignment technique. Input light from an optical fiber is first collimated, then transmitted through the isolator optics. A focusing lens on the output side of the isolator then couples the light back into the output fiber. This method is highly flexible, and allows OZ Optics to offer isolators capable of handling up to 10 Watts of optical power through singlemode fibers.

Isolators are offered in two different versions, polarization dependent and polarization independent. Both block any returning light regardless of the input polarization. However the insertion losses of polarization dependent isolators depend on the input polarization, while for polarization independent isolators the insertion losses are constant.

Polarization dependent isolators are simpler in construction. They are well suited for polarization maintaining fiber applications and for some applications where an input free space beam of constant polarization enters the Faraday optics. In either case linearly polarized light from the source or polarization maintaining fiber is aligned with the transmission axis of the isolator. However these isolators are not recommended for applications using standard singlemode fibers, as these fibers do not maintain polarization. Instead when polarized light is launched into singlemode fibers, any bends or stresses in the fiber will change the polarization state of the light traveling through the fiber. As a result, transmission through a polarization dependent isolator will vary with any bending of the fiber or changes in temperature.

In contrast a polarization independent isolator first splits the light into separate polarizations and isolates each beam separately. The two beams are then recombining and transmitted through the output fiber. This method ensures low losses regardless of the input polarization state. For this reason we recommend using polarization independent isolators with standard singlemode fibers. Please note however that polarization independent isolators are not necessarily available for all wavelengths or power levels.



Polarization Independent Isolator for 1550 nm



633-830 nm Isolator



High Power Polarization Independent Isolator for 850 nm



High Power Isolator for 980-1064 nm

Fiber Optic Isolator Product Specifications:

		Polarization Insensitive Isolators- "FOPI" Specifications				Polarization Sensitive Isolators "FOI" Specifications			
Center Wavelength ¹ λ_c (nm)		633 670	780 830 850 860	980 1064	1310 1480 1550 1590	488- 543 633 670	780 830 850	980, 1064	1310 1480, 1550, 1590
Bandwidth ² (nm)		± 10	± 10	± 10	± 10	± 10	± 10	± 10	± 10
Typical Peak Isolation (dB)		25	30	30	45 Single stage 65 Dual Stage	35	40	40	45 Single Stage 60 Dual Stage
Minimum Isolation ³ (dB)		20	25	25	40 Single Stage 60 Dual Stage	30	35	35	40 Single Stage 60 Dual Stage
Typical Insertion Loss ⁴ (dB)		1.2	0.8	0.8	0.5 Single Stage 0.6 Dual Stage	2.0	1.5	1.2	0.6 Single Stage 0.8 Dual Stage
Maximum Insertion Loss ⁴ (dB)		1.4	1.2	1.2	0.6 Single Stage 0.8 Dual Stage	2.5	1.8	1.6	0.8 Single Stage 1.0 Dual Stage
Return Loss ⁵ (dB)		40	40	40	55	40	40	40	40, 50, 60
Power Handling (Watts) ⁶	Standard	0.3	0.3	0.3	0.3	0.2	0.2	0.2	0.2
	High Power Options	0.5	0.5 1 2 5	0.5 1 2 5 10	0.5	0.5	0.5 1 2 5	0.5	0.5 1 2 5 10
PDL (dB)		0.2	0.2	0.2	0.1	NA	NA	NA	NA
Fiber Options Available		SM	SM	SM	SM	SM or PM	SM or PM	SM or PM	SM or PM
Operating Temperature (° C)		0 to +70							
Storage Temperature (° C)		-40 to +85							

Notes:

1. For other wavelengths, please contact OZ Optics.
2. This is the range of wavelengths over which the specified isolation is maintained.
3. At 23°C and $\lambda_c \pm 15\text{nm}$ and over all polarization states.
4. Over specified operating temperature range, at $\lambda_c \pm 10\text{nm}$ and over all polarization states.
5. Excluding connectors.
6. For the power handling levels, please contact OZ Optics.

Figure 1:

Theoretical Isolation Curve of Single Stage Isolator for Polarization dependent 780-980 nm Wavelengths




Figure 2:

Theoretical Isolation Curve of Dual Stage Isolator for Polarization Independent Telecom Wavelengths






Figure 3:




FIBER PIGTAILED POLARIZATION SENSITIVE AND INSENSITIVE ISOLATORS IN MINIATURE 5.5 mm OD HOUSING (FOI-21 & FOPI-21 MODELS), FOR 1064NM, 1310NM OR 1550NM WAVELENGTHS

Figure 5:




STANDARD HOUSING FOR POLARIZATION DEPENDENT (FOI-11) AND POLARIZATION INDEPENDENT (FOPI-11) ISOLATORS FOR 1064 nm, 1310 nm AND 1550 nm

Figure 4:



FIBER PIGTAILED POLARIZATION SENSITIVE ISOLATOR IN STANDARD (FOI-11) PACKAGING, FOR 630nm TO 1064nm WAVELENGTHS

Figure 6:



All units are in mm

POLARIZATION INDEPENDENT ISOLATOR (FOPI-11) FOR 830 TO 1064nm WAVELENGTHS, FOR LOW TO MEDIUM POWER APPLICATIONS

Ordering Information for Custom Parts:

Questionnaire:

1. What is the wavelength of operation?
2. What is the optical power level seen by the device?
3. Do you require polarization dependent OR polarization independent isolator?
4. What is the desired level of isolation and return losses?
5. What type of fibers do you want on the input and output ends?
6. What is the length of required pigtailed (both on input side and output side)?
7. What kind of fiber protection jacket and connector type is required?

Ordering Information:

Description

Part Number

Polarization dependent Isolator

FOI-A1-11-W-a/b-F-LB-XY-JD-L-I(-HP)

A1 = Isolator size:

- 1 for Standard size
- 2 for Miniature size (For up to 0.5 Watt power handling)

W = Wavelength: Specify in nanometers (Example: 1550 for 1550 nm)

a/b = Fiber core/cladding sizes, in microns
9/125 for 1300/1550 nm SM fiber

See Tables 1 to 5 for other standard fiber sizes

F = Fiber type: M = Multimode
S = Singlemode
P = Polarization maintaining

LB = Backreflection level: 40, 50, 55, or 60 dB
version available for 1300 nm and 1550 nm wavelengths only.

X,Y = Connector Code:

- 3S = Super NTT-FC/PC
- 3U = Ultra NTT-FC/PC
- 3A = Angled NTT-FC/PC
- 8 = AT&T-ST
- SC = SC
- SCA = Angled SC

See Table 6 for other connectors

HP = High power handling option

- HP for 0.5 Watt power handling
- HP1 for 1 Watt power handling
- HP2 for 2 Watt power handling
- HP3 for 3 Watt power handling
- HP5 for 5 Watt power handling
- HP10 for 10 Watt power handling- (Only available for selected wavelengths)

I = Peak isolation: 25, 30, 35, 40, 55, or 60 dB

L = Fiber length, in meters, on each side of the device

Example: To order 1 meter of fiber at the input and 7 meters at the output, replace L with 1,7

JD = Fiber Jacket type:

- 1 = 900 micron OD hytrel jacket
- 3 = 3 mm OD Kevlar reinforced PVC cable

See Table 7 for other jacket sizes

Note: Miniature housing size only available for 1064 nm, 1300 - 1625 nm wavelengths and for up to 0.5 W power handling.

Description

Part Number

Polarization Independent Isolator

FOPI-A1-11-W-a/b-F-LB-XY-JD-L-I(-HP)

A1 = Isolator size:

- 1 for Standard size
- 2 for Miniature size (For up to 0.5 Watt power handling)

W = Wavelength: Specify in nanometers (Example: 1550 for 1550 nm)

a/b = Fiber core/cladding sizes, in microns
9/125 for 1300/1550 nm SM fiber

See Tables 1 to 5 for other standard fiber sizes

F = Fiber type: M = Multimode
S = Singlemode
P = Polarization maintaining

LB = Backreflection level: 40, 50, 55, or 60 dB
version available for 1300 nm and 1550 nm wavelengths only.

X,Y = Connector Code:

- 3S = Super NTT-FC/PC
- 3U = Ultra NTT-FC/PC
- 3A = Angled NTT-FC/PC
- 8 = AT&T-ST
- SC = SC
- SCA = Angled SC

See Table 6 for other connectors

HP = High power handling option

- HP for 0.5 Watt power handling
- HP1 for 1 Watt power handling
- HP2 for 2 Watt power handling
- HP3 for 3 Watt power handling
- HP5 for 5 Watt power handling
- HP10 for 10 Watt power handling- (Only available for selected wavelengths)

I = Peak isolation: 25, 30, 35, 40, 55, or 60 dB

L = Fiber length, in meters, on each side of the device

Example: To order 1 meter of fiber at the input and 7 meters at the output, replace L with 1,7

JD = Fiber Jacket type:

- 1 = 900 micron OD hytrel jacket
- 3 = 3 mm OD Kevlar reinforced PVC cable

See Table 7 for other jacket sizes

Note: Miniature housing size only available for 1064 nm, 1300 - 1625 nm wavelengths and for up to 0.5 W power handling.

Ordering Examples For Standard Wavelength Parts:

Polarization Sensitive:

Type	Wavelength	Bar Code	Part Number	Description
FOI-11 FOI-21 with PM Fiber	1550	25522	FOI-11-11-1550-8/125-P-50-3U3U-3-1-40	Fiber Optic Polarization Sensitive Isolator with 1 meter long 3mm OD PVC cabled 1550nm 8/125 PM fiber pigtailed and 40dB isolation with 50dB return loss and ultra FC/PC connectors for up to 300mW
	1550	23723	FOI-21-11-1550-8/125-P-40-3S3S-3-1-40	Fiber Optic Polarization Sensitive Isolator in Small Housing with 1 meter long 3mm OD PVC cabled 1550nm 8/125 PM fiber pigtail with 40dB return loss and super FC/PC connector
	1310	19702	FOI-11-11-1310-7/125-P-40-3A3A-1-1-40	Fiber Optic Polarization Sensitive Isolator with 1 meter long 900um OD jacketed 1310nm 7/125 PM fiber pigtailed and 40dB isolation with 40dB return loss and angle FC/PC connectors
	1310	15355	FOI-21-11-1310-7/125-P-40-3SX-1-1-40	Miniature Fiber Optic Polarization Sensitive Isolator with 1 meter long 1mm OD PVC cabled 1310nm 7/125 PM fiber pigtailed and 40dB isolation with 40dB return loss and super FC/PC connector on input and output unterminated.
	1064	13401	FOI-11-11-1064-6/125-P-40-3A3A-3-1-35	Fiber Optic Polarization Sensitive Isolator with 1 meter long 3mm OD PVC cabled 980nm 6/125 PM fiber pigtailed aligned to slow axis and 35dB isolation with -40dB return loss and angle FC/PC connectors
	850	25020	FOI-11-11-850-5/125-P-40-3A3A-3-1-35	Polarization Sensitive Isolator with 1 meter long 3mm OD PVC cabled 5/125 850nm PM fiber pigtailed and 35dB isolation with 40dB return loss and angle FC/APC connectors
	633	20180	FOI-11-11-633-4/125-P-40-3A3A-3-1-35	Fiber Optic Polarization Sensitive Isolator with 1 meter long 3mm OD PVC cabled 633nm 4/125 PM fiber pigtailed and 35dB isolation with 40dB return loss and angle FC/APC connectors.
FOI-11 FOI-21 with SM Fiber	1064	16243	FOI-11-11-1064-6/125-S-40-3A3A-3-1-35	Fiber Optic Polarization Sensitive Isolator with 1 meter long 1mm OD cabled 1064nm 6/125 SM fiber pigtailed and 35dB isolation with 40dB return loss and angle FC/PC connectors
	850	31164	FOI-11-11-850-5/125-S-40-3A3A-0.25-1-35	Fiber Optic Polarization Sensitive Isolator with 1 meter long 250um acrylate jacketed 850nm 5/125 SM fiber pigtailed and 35dB isolation with 40dB return loss and angle FC/APC connectors (Similar to BC 24435)
	633	11311	FOI-11-11-633-4/125-S-40-3A3A-3-1-35	Fiber Optic Polarization Sensitive Isolator with 1 meter long 3mm OD PVC cabled 633nm 4/125 SM fiber pigtailed and 35dB isolation with 40dB return loss and angle FC/PC connectors
	514	New	FOI-11-11-514-3.5/125-S-40-3S3S-1-1-30	Fiber Optic Polarization Sensitive Isolator with 1 meter long 1mm OD PVC cabled 514nm 3.5/125 SM fiber pigtailed and 30dB isolation with 40dB return loss and super FC/PC connectors (Similar to BC 24637)

Polarization Insensitive:

Type	Wavelength	Bar Code	Part Number	Description
FOPI-11 FOPI-21 with SM Fiber	1550	20059	FOPI-11-11-1550-9/125-S-40-3A3A-3-1-40	Fiber Optic Polarization Insensitive Isolator with 1 meter long 3 mm OD PVC cabled 1550nm 9/125 SM fiber pigtailed and 40dB isolation with 40 dB return loss and angle FC/PC connectors.
	1550	27629	FOPI-21-11-1550-9/125-S-55-3A3A-1-1-55	Fiber Optic Polarization Insensitive Isolator in small (5.5 mm OD) package with 1 meter long 900 um OD jacketed 1550nm 9/125 SM fiber pigtailed and 55dB isolation with 55 dB return loss and angle FC/PC connectors
	1310	19534	FOPI-11-11-1310-9/125-S-40-3A3A-3-1-40	Fiber Optic Polarization Insensitive Isolator with 1 meter long 3mm OD PVC cabled 1310 nm 9/125 SM fiber pigtailed and 40 dB isolation with 40dB return loss and angle FC/PC connectors
	1310	31448	FOPI-21-11-1310-9/125-S-50-XX-1-1-55	Fiber Optic Polarization Insensitive Isolator in small (5.5mm OD) package with 1 meter long 900 um OD jacketed 1310nm 9/125 SM fiber pigtailed and 55dB isolation with 50 dB return loss and connectors
	1064	26506	FOPI-11-11-1064-6/125-S-40-3S3S-3-1-30	Fiber Optic Polarization Insensitive Isolator with 1 meter long, 3 mm OD jacketed, 1064nm, 6/125 μ SM fiber with film based isolator for 30 dB isolation with 40 dB return loss and super FC/PC connectors.
	1064	25561	FOPI-21-11-1064-6/125-S-40-3A3A-1-1-30	Miniature Fiber Optic Polarization Insensitive Isolator with 1 meter long 900 um OD jacketed 1064nm 6/125 SM fiber, 30 dB isolation, 40 dB return loss and Angle FC/APC connectors.
	850	24275	FOPI-11-11-855-5/125-S-40-3A3A-1-1-35	Fiber Optic Polarization Insensitive Isolator with 1 meter long 900 um OD jacketed 855nm 5/125 SM fiber pigtailed and 35 dB isolation with 40 dB return loss and Angle FC/APC connectors.