

株式会社ネオトロン

〒152-0002 東京都目黒区目黒本町 5-19-2 E-mail:sales@neotron.co.jp

NEOTRON CO., LTD.

5-19-2, MEGURO HONCHO MEGUROKU, **TOKYO 152-0002 JAPAN**



応 用

DLS 350 Application

The DLS 350 dual wavelength LED light source allows technicians to realize significant test time improvements. Used in conjunction with the RP 400 series power meters, the light source provides a 2 kHz tone output for fiber identification. The incoming 2KHz signal is identified and an audible alert is provided by the power meter. The 2KHz tone provided by the DLS 350 may also be used with non-invasive fiber identifier devices such as the LFI 110 Live Fiber Identifier from ODM.

Connection to the device under test DUT is by the male SC connector output allowing for easy cleaning of the connector surface.

ご注文方法

DLS 350 Ordering Information

Part #: DLS 350

Includes: Padded carry case, 2.5mm universal connector adapter, CR2 battery, and manual. Screw-on adapters are available for all popular connector styles. ODM's TP 200 or DLS 300-series light sources may be combined with any ODM power meter, providing a complete test kit solution.

ODM Inc. offers a complete line of <u>accessories</u> - including patch cords, adapters, and cleaning aids - for all aspects of optical testing.

Phone: 1-603-524-8350 Fax: 1-603-524-8332 sales@odm-inc.com



