

Features

- Devices may be used as multiplexer or demultiplexer
- Upgrade channel, integrated bandsplitters and tap ports available
- Multi mode fiber GI 62.5 or GI 50
- Micro-hybrid construction in a sealed metal housing
- Epoxy-free optical path
- Extremely small component dimensions: 19 x 15.5 x 9 mm³, other dimensions on request
- RoHS compliant per EU Directive 2002/95EC
- UL 94 V0 flammability rating
- Tested in accordance with Telcordia GR-1209/1221, uncontrolled environment
- Fit for outside plant deployment

Applications

- Combines / separates up to 4 channels with a 20 nm spacing
- Metro Core, Metro Access, Metro Enterprise, Cable TV, 3G Telephony (UMTS), Datacomm, WAN, RFTS, Sensor Applications
- Analog and digital transmission systems


Specifications

| Parameters | Coarse Wavelength Division Multiplexer – mux/demux (all values refer to multimode) | | |
|------------------------|--|-------------------|------------------|
| Channels | 4, 4+ upgrade | | |
| Center Wavelength [nm] | choice of 4 wavelengths within one band | | |
| Band 1 (red band) | 1471 / 1491 / 1511 / 1531 / 1551 / 1571 / 1591 / 1611 | | |
| Band 2 (blue band) | 1271 / 1291 / 1311 / 1331 / 1351 / 1371 / 1391 / 1411 / 1431 / 1451 | | |
| | Upgrade: remaining wavelengths of band | | |
| | other wavelength upon request; please contact CUBO | | |
| Optical Bandwidth | > 13 nm (higher bandwidth on request) | | |
| Insertion Loss * | 4 channel CWDM | Standard < 1.9 dB | Premium < 1.7 dB |
| | 4+ upgrade channel CWDM | Standard < 2.0 dB | Premium < 1.8 dB |
| Isolation ** | adjacent channel | > 30 dB | |
| | non-adjacent channel | > 40 dB | |
| | Isolation Spectral Range Band 1 (red) 1460-1620 nm | | |
| | Isolation Spectral Range Band 2 (blue) 1260-1460 nm | | |
| Return Loss * | > 10 dB | | |
| Directivity (for mux) | > 40 dB | | |
| Max. optical power | 250 mW | | |
| Operating Temperature | 0°C to 70°C (-40°C to 85°C on request) | | |
| Storage Temperature | -40°C to 85°C (when removed from plastic package) | | |
| Package Dimensions | 19 x 15.5 x 9 mm ³ | | |

* With passband, valid over full temperature range and at all states of polarization but without connector losses.

** Valid over full temperature range and at all wavelengths across the channel.

Additional components according to your specifications on request! Please contact Cube Optics for further details.



All information contained herein is believed to be accurate and is subject to change without notice. No responsibility is assumed for its use. Cube Optics AG, its subsidiaries and affiliates, or manufacturer, reserve the right to make changes without notice, to product design, product components and product manufacturing methods. Some specific combinations of options may not be available. Please contact Cube Optics AG for more information.




Ordering Information


CUBD

Indicate your requirements by selecting one option from each configuration table. Please write the corresponding codes in the available boxes to form your part number. For more information on this or other products and their availability, please contact Cube Optics AG at +49-6131-69851-0 or via e.mail at sales@cubeoptics.com, or visit our website at www.cubeoptics.com.


Ordering example: C-40-A-A-S-S-11-3-B-15





Further configuration on request!



Standard 4 channel housing







units [mm]

Corporate Office: Cube Optics AG Robert-Koch-Strasse 30 55129 Mainz / Germany phone: +49-6131-69851-0 fax: +49-6131-69851-79 sales@cubeoptics.com www.cubeoptics.com

Cube Optics AG

Spectral Performance