



Audio Link(Transmitter/Receiver)




➤ Main Features

- 2.2V_{p-p}(600 Ohm) input audio signals
- 20Hz ~ 20KHz bandwidth
- Transmission distance up to 80km(at 1550nm SM)
- 7~25Vdc free-volt power input
- FM, Digital modulation
- Ambient operating temperature : -40~70°C

➤ Descriptions

Cominet's Audio Link converts audio signals from microphones to optic signals and transmits up to 80km. It is free from electric noise compare to coaxial cable and has the powerful advantage that transmits multi-channels of audio signals without additional equipment through a pair of or just one optic line. FM(Frequency Modulation) type of optic link can transmits maximum 4 channels of audio signals compare with a capability of 1 channel of AM(Amplitude Modulation) type, and DM(Digital Modulation) type has the capability of 8 channels and more. Compare with two analog(AM, FM) types, DM type is immune from noise and can transmits higher quality of signals to long distance remote site.

➤ Applications



➤ Ordering Information

Mode	Model Name	Description	Fiber Count	Max. Distance
Multi Mode	A020-30T/R-80	2ch Audio uni-dir. Transmitter/Receiver DM 850nm	1	500m
	A040-30T/R-30	4ch Audio uni-dir. Transmitter/Receiver DM 1310nm	1	1 Km
	A080-30T/R-30	Max 8ch Audio uni-dir. Transmitter/Receiver DM 1310nm	1	500m
Single Mode	A040-30T/R-32	4ch Audio uni-dir. Transmitter/Receiver DM 1310nm	1	20Km
	A080-30T/R-32	Max 8ch Audio uni-dir. Transmitter/Receiver DM 1310nm	1	20Km
	A080-30T/R-54	Max 8ch Audio uni-dir. Transmitter/Receiver DM 1550nm	1	40Km
	A080-30T/R-56	Max 8ch Audio uni-dir. Transmitter/Receiver DM 1550nm	1	60Km
	A080-30T/R-58	Max 8ch Audio uni-dir. Transmitter/Receiver DM 1550nm	1	80Km

Cominet Fiber Optic Link

➤ Specifications

Specifications	Transmitter(A080-30T-xx)		Receiver(A080-30R-xx)	
	80, 31	32, 54, 56, 58	80, 31	32, 54, 56, 58
Optical Specifications				
Fiber Type	Multi-Mode	Single-Mode	Multi-Mode	Single-Mode
Number of Fiber	1 fiber			
Wavelength(nm)	850, 1310	1310,1550	850, 1310	1310,1550
Max Distance(km)	2, 4	20, 40, 60, 80	2, 4	20, 40, 60, 80
Connector	ST (FC – Option)			
Audio Input/Output Signal Specifications				
Number of Channels	1, 2, 4, 8 channels			
Audio Input/Output Signal	2.2V _{pp} (600 Ohm)			
Bandwidth	20Hz ~ 20KHz			
Signal-Noise Ratio	60dB			
Connector	RCA Jack			
Power Specifications				
Input Voltage	7~15Vdc for AM,FM type, 7~25Vdc or 12~24Vac for DM type			
Power Consumption(W)	6			
Connector	Terminal Block			
Environment Specifications				
Operating Temperature	-40°C ~ 70°C			
Storage Temperature	-50°C ~ 85°C			
Humidity	0% ~ 95%(Non-Condensing)			
Physical Specifications				
Dimension(L×W×H)	Standalone type : 180.5×118.2×39.5(mm) Rack mountable type : 19" width, 1U height Line-card type : 3U height			



Cominet Corp.

Head Office : A-606-2 Bundang Techno-park, 150 Yatap-dong Seongnam-city Kyunggi-do Korea(463-070)

Tel)+82-31-707-6460, Fax)+82-31-707-6463

<http://www.cominet.co.kr>

E-mail : info@cominet.co.kr

