



Part Number: 97-04107-01 Revision A Model Number: MHP250-6.6ADM-A1

The MHP250-6.6ADM-A1 driver is a RF driver module with Analog and Digital Modulation input and an RF output of 6.6Watts into a 50-ohm load.

Unit manufactured to be compliant with EU Directive 2002/95/EC for Reduction of Hazardous Substance (RoHS).

PARAMETER:

SPECIFICATION:

Output Frequency:	250 MHz \pm 0.01% Quartz stabilized.
Spurious Levels:	-40 dBc maximum
Harmonic Distortion:	-15 dBc maximum
Analog Input:	0-1 volt into 50 ohms 1 volt = full RF power 0 = RF power off
Digital Input:	TTL Levels TTL High = full RF power TTL Low = minimum RF power
Analog Extinction Ratio:	40 dB minimum
Digital Extinction Ratio:	30 dB minimum
RF Rise / Fall Time:	10 ns typical P _{RF} : 10 to 90 %
RF Output Power:	6.6 Watts nominal, 8 Watts maximum. Maximum output power set by internal pot.
Output Impedance:	50 ohms nominal
Supply Voltage:	+ 24 Volts DC \pm 0.5 Volt
Supply Current:	2 Amps maximum
Airflow across heat sink:	18 CFM @ +25 °C

MAXIMUM RATINGS:

Supply Voltage:	+ 28 Volts DC
Power Output:	No DC feedback allowed
Case Temperature:	+ 55 °C

CONNECTORS & MECHANICAL:

RF Output Connector:		SMA female
Modulation Input Connector:		Feed through pin
Power Supply Connections:	Vcc	Feed through pin
	Return	Feed through pin
Physical Body Size:	5.43" L x 2.42" H x 3.90" W	

RELATED DOCUMENTS:

Outline Drawing:	97-04107-01-15
------------------	----------------

For More Information, Contact: Sales@goochandhousego.com

As part of our policy of continuous product improvement we reserve the right to change specifications at any time.