

长春新产业光电技术有限公司

Changchun New Industries Optoelectronics Tech. Co., Ltd.

DATA SHEET

AO-W-532 /1~300uJ/1~2W

LD PUMPED ALL-SOLID-STATE AOM Q-SWITCHEDLASER AT 532 nm

All solid state AOM Q-switched laser at 532 nm has the features of high peak power, high repetition rate, and short pulse duration, which is widely used in marking, carving, measure, research and so on.



Wavelength (nm)	532±1		
Operating mode	Q-switched: AOM (Acousto-Optic Modulation)		
Single pulse energy(uJ)	1~300		
Pulse duration (ns)	5~30		
Peak power (kW)	10~30		
Rep. rate (kHz)	1~50, 1~100, 1~200, optional		
Average power (W)	Average power (W) = Single pulse energy (mJ) * Rep. rate (kHz)		
	>65% @10kHz, typical		
Ave power stability (over 4 hours)	<3%, <5%, <10%		
Warm-up time (minutes)	<10		
Beam divergence, full angle (mrad)	<2.0		
Beam diameter at the aperture (mm)	~4.0		
Beam height from base plate (mm)	93.5		
Cooled method	Air cooled		
Operating temperature (°C)	15~35		
Power supply (220/110VAC)	PSU-AOM		
Expected lifetime (hours)	10000		
Warranty period	1 year		





AO-W-532	Dimensions	PSU-AOM	Dimensions
نام المراب نام المراب 333(L)×140(W) ×125(H) mm³, 6.0 kg		DPSSL DRIVER UPSSL DRIVER	