

长春新产业光电技术有限公司

Changehun New Industries Optoelectronics Tech. Co., Ltd.

DATA SHEET

AO-W-946 /1uJ~150uJ/1~1500mW

SPECIFICATIONS

LD PUMPED ALL-SOLID-STATE AOM Q-SWITCHED LASER

All solid state AOM Q-switched laser at 946 nm has the features of high peak power, high repetition rate, and short pulse duration, which is widely used in marking, carving, measure, research and so on.



Wavelength (nm)	946±1	
Operating mode	Q-switched: AOM (Acousto-Optic Modulation)	
Output power	1~1500mW	
Single pulse energy (µJ)	1~50	
Pulse duration (ns)	~30@10kHz	
Peak power (kW)	~3	
Rep. rate (kHz)	1~50, adjustable by external control	
Ave power stability (over 4 hours)	<1%,<3%, <5%, <10%	
Warm-up time (minutes)	<10	
Beam divergence, full angle (mrad)	<2.0	
Beam diameter at the aperture (mm)	~4.0	
Beam height from base plate (mm)	93.5	
Cooled method	Air cooled	
Operating temperature (°C)	10~35	
Power supply (220/110VAC)	PSU-AOM(3U)	
Expected lifetime (hours)	10000	
Warranty period	1 year	





AO-W-946	Dimensions	PSU-AOM(3U)	Dimensions
نام المراب 333(L)×140(W) ×125(H) mm³, 6.0 kg		485(L) ×381(W) ×133 (H) mm ³ , 12.4 kg	