



MDL-H-880/1~2500mW

## **INFRARED DIODE LASER AT 880nm**

Diode infrared laser module at 880nm is made features of ultra compact, long lifetime, low cost and easy operating, which is used in measurement, communication, spectrum analysis, etc.



## SPECIFICATIONS

|   |   |
|---|---|
| Wavelength (nm)                         | 880±3   |
| Output power (mW)                       | >1, 100, 200, ..., 2500                                   |
| Transverse mode                         | Near TE <sub>00</sub>                                     |
| Operating mode                          | CW  |
| Power stability (rms, over 4 hours)     | <1%, <3%, <5%   |
| Warm-up time (minutes)                  | <5  |
| M <sup>2</sup> factor                   | <20   |
| Beam divergence, full angle (mrad)      | <3.0  |
| Beam diameter at the aperture (mm)      | 5~8   |
| Beam height from base plate (mm)        | 29  |
| Pointing stability after warm-up (mrad) | <0.05   |
| Operating temperature (°C)              | 10~35   |
| Power supply (90-264VAC)                | PSU-H-LED   |
| Modulation option                       | TTL/Analog 1Hz-5KHz, 1Hz-10KHz, 1Hz-30KHz, and TTL on/off |
| Expected lifetime (hours)               | 10000   |
| Warranty period                         | 1 year  |



| MxL-H-880   | PSU-H -LED   | PSU-H-FDA   | PSU-H-OEM   |
|---|--|---|---|
|  |  |  |  |
| 153(L)×77(W)×60(H) mm <sup>3</sup> , 0.9 kg                                       | 268 (L) ×145(W) ×106 (H) mm <sup>3</sup> , 2.6 kg                                  | 238 (L) ×146(W) ×102 (H) mm <sup>3</sup> , 2.3 kg                                   | 238 (L) ×146(W) ×94 (H) mm <sup>3</sup> , 2.2 kg                                    |