

MDL-III-375/1~150mW

UV LASER AT 375 nm


UV laser module at 375 nm is made features of ultra compact, long lifetime, low cost and easy operating, which is used in medical imaging, flow cytometry, DNA sequencing, etc.



SPECIFICATIONS

Wavelength (nm)	375±5	
Output power (mW)	>1, 10, 50, ..., 150	
Transverse mode	Near TEM ₀₀	
M ² factor	<1.3	
Operating mode	CW	
Power stability (rms, over 4 hours)	<5%, <3%, 1%	
Warm-up time (minutes)	<5	
Beam divergence, full angle (mrad)	~1.0	
Beam diameter at the aperture (mm)	3.0×5.0, elliptical	
Polarization ratio	>100:1	
Beam height from base plate (mm)	24.8	
Pointing stability after warm-up (μrad/°C)	<6	
Operating temperature (°C)	10~45	
Power supply (90-264VAC)	PSU-III-LED	PSU-III-FDA
Modulation option	TTL/Analog 1Hz-5KHz, 1Hz-10KHz, 1Hz-30KHz, and TTL on/off	
Expected lifetime (hours)	10000	
Warranty period	1 year	



MxL-III-375	PSU-III-LED	PSU-III-FDA
 <p style="text-align: center;">139(L)×73(W)×46.2(H) mm³, 0.6kg</p>	 <p style="text-align: center;">153 (L) ×155(W) ×92 (H) mm³, 1.5kg</p>	 <p style="text-align: center;">133 (L) ×130(W) ×65 (H) mm³, 1.2kg</p>
		