

MGL-N-543/200~1500mW

LD PUMPED ALL-SOLID-STATE GREEN LASER AT 543nm

All solid state laser at 543nm is made features of ultra compact, long lifetime, low cost and easy operating, which is used in scientific experiment, optical sensor, measurement, instrument, communication, spectrum analysis, etc.



SPECIFICATIONS

Wavelength (nm)	543±1		
Output power (mW)	>200, 300, 400, ... , 1500		
Transverse mode	Near TEM ₀₀		
Operating mode	CW		
Power stability (rms, over 4 hours)	<3%, <5%, <10%		
Warm-up time (minutes)	<10		
M ² factor	<3.0		
Beam divergence, full angle (mrad)	<1.5		
Beam diameter at the aperture (mm)	~3.0		
Beam height from base plate (mm)	68.2		
Polarization ratio	>100:1		
Operating temperature (°C)	10~35		
Power supply (90-264VAC)	PSU-H-LED	PSU-H-FDA	PSU-N-OEM
Modulation option	TTL on/off, 1Hz-1KHz, 1KHz-10KHz, 10KHz-30KHz; and Analog modulation option		
Expected lifetime (hours)	10000		
Warranty period	1 year		



MGL-N-543	PSU-H-LED	PSU-H-FDA	PSU-N-OEM
 240(L)×99(W)×94(H) mm³, 2.6 kg	 268 (L) ×145(W) ×106 (H) mm³, 2.6 kg	 238 (L) ×146(W) ×102 (H) mm³, 2.3 kg	 215 (L) ×129 (W) ×122 (H) mm³, 2.145 kg
			