

MGL-W-515/200~500mW

LD PUMPED ALL-SOLID-STATE GREEN LASER




All solid state 515nm green laser is made features of ultra compact, long lifetime, low cost and easy operating, which is widely used in collimation, laser medical treatment, scientific experiment, optical instrument, laser display, laser lighting show, etc.



SPECIFICATIONS

Wavelength (nm)	515±1	
Output power (mW)	>200, 300, 400, ..., 500	
Transverse mode	Near TEM ₀₀	
Operating mode	CW	
Power stability (rms, over 4 hours)	<5%, <10%	
Warm-up time (minutes)	<10	
M ² factor	<3.0	
Beam divergence, full angle (mrad)	<2.0	
Beam diameter at the aperture (mm)	~3.0	
Beam height from base plate (mm)	93.5	
Polarization ratio	>100:1	
Operating temperature (°C)	10~35	
Power supply (90-264VAC)	PSU-W-LED	PSU-W-FDA
Modulation option	TTL on/off, 1Hz-1KHz, 1KHz-10KHz, 10KHz-30KHz; and Analog modulation option	
Expected lifetime (hours)	10000	
Warranty period	1 year	



MxL-W-515	PSU-W-LED	PSU-W-FDA
 <p>333(L)×140(W)×125(H) mm³, 6.1 kg</p>	 <p>300 (L) ×162(W) ×134(H) mm³, 5.2 kg</p>	 <p>307 (L) ×168(W) ×123(H) mm³, 5.1 kg</p>
