



MIL-H-914/500~800mW

### LD PUMPED ALL-SOLID-STATE INFRARED LASER AT 914nm





All solid state infrared laser at 914nm is made features of ultra compact, long lifetime, low cost and easy operating, which is used in scientific experiment, optical instrument, optical sensor, measurement, communication, spectrum analysis, etc.



#### SPECIFICATIONS

Wavelength (nm)	914±1		
Output power (mW)	>500, 550, 600, ... ,800		
Transverse mode	Near TEM <sub>00</sub>		
Operating mode	CW		
Power stability (rms, over 4 hours)	<5%, <10%		
Warm-up time (minutes)	<10		
M <sup>2</sup> factor	<2.0		
Beam divergence, full angle (mrad)	<2.0		
Beam diameter at the aperture (mm)	~3.0		
Beam height from base plate (mm)	29		
Polarization ratio	>100:1		
Pointing stability after warm-up (mrad)	<0.05		
Operating temperature (°C)	10~35		
Power supply (90-264VAC)	PSU-H-LED	PSU-H-FDA	PSU-H-OEM
Expected lifetime (hours)	10000		
Warranty period	1 year		



MxL-H-914	PSU-H-LED	PSU-H-FDA	PSU-H-OEM
 153(L)×77(W)×60(H) mm <sup>3</sup> , 0.9 kg	 268(L)×145(W)×106(H) mm <sup>3</sup> , 2.6 kg	 238 (L)×146(W)×102 (H) mm <sup>3</sup> , 2.3 kg	 238 (L)×146(W)×94 (H) mm <sup>3</sup> , 2.2 kg
