



MLL-III-705 / 1~25mW

**LOW NOISE RED DIODE LASER
At 705nm**

Low noise red diode laser at 705nm is made features of round spot, long lifetime, low cost and easy operating, which is widely used in measurement, spectrum analysis, etc.



SPECIFICATIONS

Wavelength (nm)	705 ± 10	
Output power (mW)	>1, 5, 10, ..., 25	
Transverse mode	Near TEM ₀₀	
Operating mode	CW	
Power stability (rms, over 4 hours)	<1%, <3%, <5%	
Noise of amplitude (rms, 1~20MHz)	<1%	
Coherence length (cm)	20	
Warm-up time (minutes)	<5	
Beam divergence, full angle (mrad)	<1.0	
Dimensions of beam at the aperture (mm)	~3. 0	
Beam height from base plate (mm)	24.8	
Operating temperature (°C)	10~35	
Power supply (90-264VAC)	PSU-III-FDA	PSU-III-LED
Warranty	1 year	



MLL-III-705	PSU-III-LED	PSU-III-FDA
 <p>139(L)×73(W)×46.2(H) mm³, 0.6kg</p>	 <p>153 (L) ×155(W) ×92 (H) mm³, 1.5kg</p>	 <p>133 (L) ×130(W) ×65 (H) mm³, 1.2kg</p>
		