

PGL-III-D-532/1~200mW (each end)

PORTABLE GREEN LASER AT 532nm

PGL-III-D 532nm is made features of small size, high output power, long lifetime in portable laser, which can emit laser in both ends. It is specially designed for the laser show application.



SPECIFICATIONS

| | | |
|------------------------------------|---|--------------|
| Model | PGL-III-D-532 | |
| Wavelength (nm) | 532 ± 1 | |
| Output power (mW) | >1, 5, 10, ..., 100 | >100.....200 |
| Transverse mode | TEM ₀₀ | |
| Operating mode | CW | |
| Beam divergence, full angle (mrad) | <1.2 | |
| Beam diameter at the aperture (mm) | ~5.0 | |
| Switch | Push button | |
| Surface color | Black | |
| Power supply | Built-in Charged Power Supply | |
| Expected lifetime (hours) | 5000 | |
| Warranty | 6 months | |
| Remark | Red laser at 640 nm and blue laser at 447nm are available upon request. | |
| Weight (kg) | 0.25 | |



| PGL-III-D-532 (front-end) | PGL-III-D-532 (back-end) | PGL-III-D-532 (both ends) |
|--|--|---------------------------|
| | | |
| Dimensions | | Accessory |
| <p style="text-align: center;">1-100mW</p> | <p style="text-align: center;">100-200mW</p> | |