

EyeSafe Delivery Fibers

Nufern has specifically engineered a unique range of single-mode 2µm beam delivery fibers for the long wavelength EyeSafe window from 1850-2200nm, available in both PM and non-PM versions. By applying our extensive fiber manufacturing expertise, gained in the demanding telecommunications industry, this family of fibers has excellent uniformity and high fatigue failure resistance. These fibers are aimed at emerging fiber applications for the 2µm wavelength, including medical, military/aerospace and industrial fiber laser markets.

Typical Applications

- Pigtailing 2µm components
- Tm-fiber lasers/amplifiers
- 2µm beam delivery

Features & Benefits

- Optimized for 2µm wavelengths Higher performance
- Low bend loss at 2µm Tighter packaging
- Tight tolerances High product yield

Optical Specifications

Operating Wavelength Core NA Mode Field Diameter

Cutoff Beat Length (nominal) Birefringence

Geometrical & Mechanical Specifications

Cladding Diameter Core Diameter **Coating Diameter Coating Concentricity** Core/Clad Offset Coating Material **Operating Temperature Range** Prooftest Level

1850 – 2200 nm
0.200
8.0 µm @ 1950 nm
(nominal)
1720 ± 80 nm
N/A

SM1950

7.0 µm

< 5.0 µm

≤ 0.50 µm

-40 to 85 °C

PM1950

0.200

1850 - 2200 nm

8.0 um @ 1950 nm (nominal)

5.2 mm @ 1950 nm

nominal 3.5 × 10⁻⁴

1720 ± 80 nm

1850 – 2200 nm
0.200
8.0 µm @ 1950 nm
(nominal)
1720 ± 80 nm
N/A
N/A

125.0 ± 1.0 µm 125.0 ± 1.0 µm 7.0 µm 245.0 ± 15.0 µm 245.0 ± 15.0 µm < 5.0 µm ≤ 0.50 µm UV Cured, Dual Acrylate UV Cured, Dual Acrylate -40 to 85 °C \geq 100 kpsi (0.7 GN/m²) ≥ 100 kpsi (0.7 GN/m²)



7 Airport Park Road. East Granby. CT 06026 • 860.408.5000 • Toll-free 866.466.0214 • Fax 860.844.0210 E-mail info @ nufern.com • www.nufern.com Nufern products are manufactured under an ISO 9001:2008 certified quality management system.



Standard specifications and design parameters are listed above. Specifications are subject to change without notice. Other configurations such as alternative form factors, optimized cut-off and UV cured color coating may be available. Let us know how Nufern can assist with your requirements.