

# 980/1060 nm Select Cutoff Single-Mode Fiber

Nufern's 1060-XP select cutoff single-mode fibers are optimized for use by component manufacturers in the telecommunications wavelengths. These application-specific fibers were developed for pump diode pigtails, unique delivery for components and couplers. They offer exceptional uniformity and core/clad concentricity specifications, very tight second mode cut off tolerances, and tighter bend radius for applications in optical packages. These extra high-performance specifications result in superior strength, increased component reliability, improved production yields and reduced component manufacturer costs.

# **Typical Applications**

- Pump Diode Pigtails
- 980/1550 nm WDM Couplers
- Single Clad Yb-fiber pigtails

## **Features & Benefits**

- Exceptional uniformity and core/clad concentricity Low, consistent splice loss to telecom components
- Extremely tight second mode cutoff tolerance High yield coupler manufacturing
- Higher proof test levels Critical for long-term reliability in tight bend applications

### **Optical Specifications**

Operating Wavelength Core NA Mode Field Diameter

> Cutoff Core Attenuation

### Geometrical & Mechanical Specifications

Cladding Diameter Core Diameter Coating Diameter Coating Concentricity Core/Clad Offset Coating Material Operating Temperature Range Short Term Bend Radius Long Term Bend Radius Prooftest Level  $\begin{array}{l} 980 - 1600 \text{ nm} \\ 0.140 \\ 5.9 \pm 0.5 \ \mu\text{m} @ 980 \text{ nm} \\ 6.2 \pm 0.5 \ \mu\text{m} @ 1060 \text{ nm} \\ 9.5 \pm 0.5 \ \mu\text{m} @ 1550 \text{ nm} \\ 920 \pm 30 \text{ nm} \\ \leq 1.5 \ \text{dB/km} @ 1060 \text{ nm} \\ \leq 2.1 \ \text{dB/km} @ 980 \text{ nm} \end{array}$ 

1060-XP

125.0 ± 0.5 μm 5.8 μm 245.0 ± 10.0 μm < 5.0 μm ≤ 0.30 μm UV Cured, Dual Acrylate -55 to 85 °C ≥ 6 mm ≥ 13 mm ≥ 200 kpsi (1.4 GN/m²)



7 Airport Park Road, East Granby, CT 06026 • 860.408.5000 • Toll-free 866.466.0214 • Fax 860.844.0210 E-mail info @ nufern.com • www.nufern.com Nufern products are manufactured under an ISO 9001:2008 certified quality management system.



Standard specifications and design parameters are listed above. Specifications are subject to change without notice. Other configurations such as alternative form factors, optimized cut-off and UV cured color coating may be available. Let us know how Nufern can assist with your requirements.