

Planar Waveguide Single-Mode Fiber



Nuferm extra high-performance Planar Waveguide Fiber provides a solution to the splicing challenges for high NA waveguiding structures. Industry developments indicate the call out for easy interfacing of new planar waveguide (PWG) technology with existing fiber infrastructures. Planar Waveguide Fiber is an excellent bridge fiber between high NA planar waveguides and low NA transmission fiber. This fiber allows outstanding optical coupling with planar waveguides. In addition, the composition of PWG1-XP is tailored to thermally expand the core during splicing and thus achieve low splice loss to transmission fibers.

Typical Applications

- Fibertails for Planar Waveguides
- Bridge Fiber

Features & Benefits

- High numerical aperture — Bend insensitive fiber for miniature packages
- Thermally expandable core — Low splice loss to transmission fiber
- Small Mode Field Diameter — High coupling efficiency with Planar Waveguides

Optical Specifications

Operating Wavelength (nominal)	1550 nm
Core NA	0.260
Mode Field Diameter	4.8 ± 0.5 μm @ 1550 nm
Cutoff	1330 ± 50 nm

PWG1-XP

Geometrical & Mechanical Specifications

Cladding Diameter	125.0 ± 0.5 μm
Core Diameter	3.7 μm
Coating Diameter	245.0 ± 10.0 μm
Coating Concentricity	< 5.0 μm
Core/Clad Offset	≤ 0.30 μm
Coating Material	UV Cured, Dual Acrylate
Operating Temperature Range	-55 to 85 °C
Short Term Bend Radius	≥ 6 mm
Long Term Bend Radius	≥ 13 mm
Proof test Level	≥ 200 kpsi (1.4 GN/m ²)



7 Airport Park Road, East Granby, CT 06026 • 860.408.5000 • Toll-free 866.466.0214 • Fax 860.844.0210 E-mail info @ nuferm.com • www.nuferm.com Nuferm products are manufactured under an ISO 9001:2008 certified quality management system.



Standard specifications and design parameters are listed above. Specifications are subject to change without notice. Other configurations such as alternative form factors, optimized cut-off and UV cured color coating may be available. Let us know how Nuferm can assist with your requirements.