

UBLeds[®] SMD PLCC LED Products

5050 Type



TAxx5050Dx Series	Dimension(mm)	Power Dissipation(W)	Color	Luminous Intensity Iv (mcd)	View Angle
	5.0 * 5.0 * 1.5	0.2	W/WW/R/G B/Y/O/RGB	520~7200	120°

TCxx5050Dx Series	Dimension(mm)	Power Dissipation(W)	Color	Luminous Intensity Iv (mcd)	View Angle
	5.0 * 5.0 * 1.5	0.4	W/WW	4250~7200	120°



SDxx5050Dx Series	Dimension(mm)	Power Dissipation(W)	Color	Luminous Intensity Iv (mcd)	View Angle
	5.0 * 5.1 * 1.3	0.6~0.95	W/WW/R/G B/Y/RGB	1650~30000	120°

SExx5050Dx Series	Dimension(mm)	Power Dissipation(W)	Color	Luminous Intensity Iv (mcd)	View Angle
	5.0 * 5.1 * 1.3	1.2~1.6	W/WW	12000~40000	120°


5074 Type



SExx5074Dx Series	Dimension(mm)	Power Dissipation(W)	Color	Luminous Intensity Iv (mcd)	View Angle
	5.0 * 7.4 * 1.3	1.0~1.4	W/WW/R/Y	2500~30000	120°

SDxx5074Dx Series	Dimension(mm)	Power Dissipation(W)	Color	Luminous Intensity Iv (mcd)	View Angle
	5.0 * 7.4 * 1.3	0.5~0.8	W/WW/R/G B/Y/O/RGB	2000~30000	120°

3528 Type



TAxx388Dx Series	Dimension(mm)	Power Dissipation(W)	Color	Luminous Intensity Iv (mcd)	View Angle
	3.5 * 2.8 * 1.9	0.1	W/WW/RGB	1650~2500	120°



TAxx118Dx Series	Dimension(mm)	Power Dissipation(W)	Color	Luminous Intensity Iv (mcd)	View Angle
	3.5 * 2.8 * 1.9	0.12	W/WW	1650~2500	120°

TBxx118Dx Series	Dimension(mm)	Power Dissipation(W)	Color	Luminous Intensity Iv (mcd)	View Angle
	3.5 * 2.8 * 1.9	0.06	W/WW/R/G B/Y/O/RGB	80~2500	120°

3020 Type



TBxx518Dx Series	Dimension(mm)	Power Dissipation(W)	Color	Luminous Intensity Iv (mcd)	View Angle
	3.0 * 2.0 * 1.3	0.06	W/WW/R G/B/Y/O	80~2500	120°

Side View Type



SLxx8xxAx Series	Dimension(mm)	Power Dissipation(W)	Color	Luminous Intensity Iv (mcd)	View Angle
	4.0 * 1.4 * 0.8	0.05	W/WW/R G/B/Y/O	80~2050	120°



TBxx518Dx Series	Dimension(mm)	Power Dissipation(W)	Color	Luminous Intensity Iv (mcd)	View Angle
	3.8 * 1.2 * 0.6	0.05	W/WW/R G/B/Y/O	80~2050	120°